

PERFORMANCE TRUCK - HOUSTON

6855 North Loop 610 East, Houston, Texas 77028

Phone: (713) 844-7111

BUYER'S ORDER

Date Prepared: 11-16-2018	Delivery Date: 05-15-2018	Salesman: Preston Fredrich	Branch: Houston
Purchaser: League City	Telephone:	Fax:	
Mailing Address:	City: League City State: TX Zip:	County:	
Physical Address:	City: League City State: TX Zip:	County:	
Description: NEW 2020 KENWORTH T440			
Mileage:	Color: L0006 White	NOTE: BUYBOARD CONTRACT# 521-16	
VIN: TO ORDER Comments: See attached vehicle summary, quote ID # Q02035278.			
Purchaser's Agent: Chris Svahn	Title:	License Type: Apportioned	Account # Leage City

LICENSE - TITLE INFORMATION

Months: 12	Tractor:	Truck: X	Trailer:	Body Type: TANK	Color: WHI	Tons:	GCW: 66000
Apportioned: X	IMC #	Combination:	Com'l:	Token Trailer:	Gas:	Diesel: X	

INSURANCE INFORMATION

AGENCY:	SELLING PRICE	404,021.16
NAME:	PHONE:	BUYBOARD FEE
		400.00

LIEN INFORMATION

NAME:	LIEN DATE:	CASH PRICE W/ACCESS.	404,421.16
ADDRESS:	PHONE:	TRADE IN ALLOWANCE	-
CITY, STATE, ZIP:		NET CASH DIFFERENCE	404,421.16
COMMENTS:		FEDERAL RETAIL EXCISE TAX	-
AMOUNT:	NAME:	NET PRICE	404,421.16
		STATE SALES TAX	-

ADDITIONAL INFORMATION

BUYBOARD CONTRACT #521-16	TITLE FEE (INCLUDES \$5 TAG FEE)	5.00
Proposal is for one Kenworth T440 Vactor Unit	COMMERCIAL INSPECTION FEE	-
6x4 Daycab - Full Specifications are Attached	DEALER'S INVENTORY TAX	851.31
Pricing is Per Unit	DOCUMENTARY FEE*	75.00
PAYMENT IN FULL AT TIME OF DELIVERY	EXTENDED WARRANTY	-
Standard Warranty Applies	SUBTOTAL	405,352.47
	BALANCE OWED ON TRADE	-
	SUBTOTAL	405,352.47
	PREPAYMENT	-
	BALANCE DUE UPON DELIVERY	405,352.47

DISCLAIMER OF WARRANTY

Any warranties on the products sold hereby are those made by the manufacturer. The seller, CLEVELAND MACK SALES, INC., PERFORMANCE TRUCK OR PERFORMANCE TRAILER, hereby expressly disclaims all warranties, either express or implied, including any implied warranty of merchantability or fitness for a particular purpose, and CLEVELAND MACK SALES, INC., PERFORMANCE TRUCK OR PERFORMANCE TRAILER neither assumes nor authorizes any other person to assume for it any liability in connection with the sale of said products.

* A DOCUMENTARY FEE IS NOT AN OFFICIAL FEE. A DOCUMENTARY FEE IS NOT REQUIRED BY LAW, BUT MAY BE CHARGED TO BUYERS FOR HANDLING DOCUMENTS RELATING TO THE SALE. A DOCUMENTARY FEE MAY NOT EXCEED A REASONABLE AMOUNT AGREED TO BY THE PARTIES. THIS NOTICE IS REQUIRED BY LAW.

Vehicle(s) are subject to prior sale and will not be held more than five working days.

PURCHASER _____

THIS ORDER NOT BINDING UNTIL ACCEPTED BY DEALER.

SALESPERSON _____

ACCEPTED BY _____



Performance Truck C359
6855 North Loop East

Kinloch Equipment - Vactor
3320 Pasadena Blvd.

Houston, Texas United States 77028

Phone: (361) 798-0902

Fax:

Email: pfredrich@performancetruck.com

Pasadena, Texas United States 77503

Phone: (281) 369-2200

Fax:

Contact Email:

Prepared for: Todd Kinloch

Vehicle Summary

Unit		Chassis	
Model:	T400 Series Conventional.	Fr Axle Load (lbs):	20000
Type:	FULL TRUCK	Rr Axle Load (lbs)	46000
Description:	T440	G.C.W. (lbs):	66000
Application		Road Conditions:	
Intended Serv.:	Local pickup & delivery.	Class A (Highway)	88
Commodity:	Vehicles which haul	Class B (Hwy/Mtn)	10
	Other bulk goods	Class C (Off-Hwy)	02
Body		Class D (Off-Road)	00
Type:	Tank	Maximum Grade:	6
Length (ft):	23.0	Wheelbase (in):	260
Height (ft):	12.0	Overhang (in):	71
Max Laden Weight (lbs):	4000	Fr Axle to BOC (in):	67
Trailer		Cab to Axle (in):	193
No. of Trailer Axles:	0	Cab to EOF (in):	264
		Overall Comb. Length (in):	381
Type:		Special Req.	
Length (ft):	0.0	U.S. Domestic Registry, 50-State	
Height (ft):	0.0		
Kingpin Inset (in):	0		
Corner Radius (in):	0		
Restrictions			
Length (ft):	120		
Width (in):	102		
Height (ft):	13.5		

Approved by: _____

Date: _____

Note: All sales are F.O.B. designated plant of manufacture.

	Ask your dealer for a quote today, or visit our website @ www.paccarfinancial.com .
	PACCAR Financial offers innovative finance, lease and insurance programs customized to meet your needs.

Unpublished options may require review/approval.

Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed: 11/7/2018 8:20:55 AM

Effective Date: Jan 1, 2019

Prepared by: Preston Fredrich

Complete

Model Number: T400 Series Conventional.

Quote/DTPO/CO: Q02035278

Version Number: 43.01



Performance Truck C359
6855 North Loop East

Kinloch Equipment - Vactor
3320 Pasadena Blvd.

Houston, Texas United States 77028

Phone: (361) 798-0902

Fax:

Email: pfredrich@performancetruck.com

Pasadena, Texas United States 77503

Phone: (281) 369-2200

Fax:

Contact Email:

Prepared for: Todd Kinloch

	Description	Weight
Model		
	T400 Series Conventional.	11,518
	T440 6x4 Class 8	0
	Chassis operation will include stationary application used in lower 48 states [US only]. Stationary operation is defined as running the engine under load while stationary at a substantial fraction of engine gross horsepower (60% or greater) for an extended period of time (longer than 5 - 10 minutes).	0
	CARB Idle Emissions Reduction Feature for PX-7 and PX-9	0
	T440 6x4 Class 8	0
	Other bulk goods	0
	Local pickup & delivery. Vehicles which haul freight, typically operating within a 100-mile radius, on public streets & highways, & other paved surfaces, including limited Class C roads. Includes package & freight delivery, as well as fuel oil or petroleum distribution, etc. Road usage: minimum 3% Class B, do not code for Class D.	0
	Tank	0
	U.S. Domestic Registry, 50-State	0

Engine & Equipment

PACCAR PX-9 380 2017 380@1900 1250@1400

Includes turbo exhaust brake, no code is used. Diagnostic Plug for data link, Oil Cooler, Aluminum Flywheel Housing.

N09200 N205 68...Standard Maximum Speed Limit [LSL]

N09220 N207 0....Expiration Distance

N09260 P14 64...Maximum Accelerator Pedal Vehicle Speed

N09300 P19 64...Maximum Cruise Speed

N09360 N203 252...Reserve Speed Function Reset Distance

N09380 N202 0....Maximum Cycle Distance

N09400 N206 10...Maximum Active Distance

N09420 N201 0....Reserve Speed Limit Offset

N09440 P11 YES...Engine Protection Shutdown

N09460 P06 NO...Gear Down Protection

N09480 P26 1400.Max PTO Speed

N09500 P02 YES...Cruise Control Auto Resume

N09520 P04 NO...Auto Engine Brake in Cruise

N09540 N209 0....Expiration Distance

Unpublished options may require review/approval.

Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed: 11/7/2018 8:20:55 AM

Effective Date: Jan 1, 2019

Prepared by: Preston Fredrich

Complete

Model Number:

Quote/DTPO/CO:

Version Number:

T400 Series Conventional.

Q02035278

43.01

Description		Weight
N09560	P520 YES..Enable Idle Shutdown Park Brake Set	
N09580	P32 5....Timer Setting	
N09600	P233 YES..Enable Impending Shutdown Warning	
N09620	P234 60....Timer For Impending Shutdown Warning	
N09640	P516 35...Engine Load Threshold	
N09680	P33 NO...Idle Shutdown Manual Override	
N09720	P230 YES..Enable Hot Ambient Automatic Override	
N09740	P46 40...Low Ambient Temperature Threshold	
N09760	P56 60...Intermediate Ambient Temperature Threshold	
N09780	P47 80...High Ambient Temperature Threshold	
Prospector Version 43.0		0
Replaces 42.1		
Enable engine regeneration in PTO mode Cummins		0
Effective VSL Setting NA		0
Engine Idle Shutdown Timer Disabled		0
Enable EIST Ambient Temp Override		0
Enable EIST in PTO Mode		0
Use only with MX and Cummins engines		
Eff EIST NA Expiration Miles		0
Use only with MX and Cummins engines		
Air compressor: Cummins 18.7 CFM For Cummins And		0
PACCAR PX engines.		
Engine mount Powercore air cleaner.		0
w/constant torque SS clamps, pop-up air restriction indicator. Pop-up indicator is standard.		
Fan Hub: Horton 2-Speed for ISL9, ISL-G,		0
PX-8 or PX-9		
Cooling module: 1300 square inches.		0
Includes aluminum radiator core, aluminum charge air cooler, translucent surge tank and washer bottle, silicone hoses, and extended life coolant. Drain valve is not available w/Allison transmissions.		
Exhaust: 2017 EPA RH Under DPF/SCR w/ RH		0
side of cab vertical tailpipe w/ daycabs, extended daycabs, or modular sleepers.		
Tailpipe 5" Single 18"		0
Fuel Filter:Fleetguard FS1003		0
Fuel/Water Separator for PX-9		
Run Aid:None		0
*For Fuel Filter		
Start Aid:None		0
*For Fuel Filter		
Kenworth Fuel Cooler		0
Required for Cummins engines with a single fuel tank. Required for PACCAR MX-13 engine with a single fuel tank and stationary use: High RPM, low vehicle speed, sustained for longer than 1 hour. Optional for all other applications.		

Unpublished options may require review/approval.

Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed: 11/7/2018 8:20:55 AM
Effective Date: Jan 1, 2019
Prepared by: Preston Fredrich

Complete

Model Number: T400 Series Conventional.
Quote/DTPO/CO: Q02035278
Version Number: 43.01



Description	Weight
Immersion block heater 120V 1000W w/plug under door on C500, T660, T800 & W900.	0
Shutoff Valves for trailer heat with hoses routed	0
Alternator: PACCAR 160 amp, brush type	0
Batteries: 2 PACCAR GP31 threaded post (1000) 2000 CCA starting.	4
Starter: PACCAR 12 volt electrical system. W/ centralized power distribution incorporating plug-in style relays. Circuit protection for serviceability, 12-volt light system w/circuit protection circuits number & color coded.	0
Multi-function engine connector for body builder interface for Cummins.	0
Jump start terminals under hood.	12
J1939 HARNESS EXTENSION UNDER HOOD AT FIREWALL, DRIVER SIDE	0
Transmission & Clutch	
Transmission: Fuller FRO14210C 10-speed Standard with synthetic lubricant. Includes severe-duty pilot bearing on all class 8 models. *Torque Limit: 1450 pound-feet.	0
Clutch: Eaton 15-1/2 in. Advantage Self-Adjust to 1700 ft-lb, Ceramic, 4-Paddle	5
Driveline: 3 Meritor RPL25; 2 Centerbearing Require 3500058	170
Chassis will be fitted w/ LH transmission PTO. (Prevents ECU F/Interfering w/ PTO Only).	0
Actual Code 2429101 Chassis will be fitted with RH transmission PTO	0
Front Axle & Equipment	
PACCAR Front Axle rated at 20K, standard track, 4 in. drop.	156
Front Brakes: 22K Bendix ES S-cam 16.5x6 in.	-46
Front Brake Drum: 22,000 lbs. 16-1/2x6 in. Cast.	104
Front Hubs Iron hub pilot 22,000 lbs. 10 Bolt 16.5x6in. or 7in. or air disc brakes. 10 Bolt, 11-1/4 in. bolt circle. Consider Wheelguards (5850002) with aluminum wheels.	80
ConMet PreSet Plus Hub package; front axle.	0
Hubcap: front vented.	0
Front Auto Slack Adjuster.	0

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed: 11/7/2018 8:20:55 AM
Effective Date: Jan 1, 2019
Prepared by: Preston Fredrich

Complete

Model Number: T400 Series Conventional.
Quote/DTPO/CO: Q02035278
Version Number: 43.01



Description	Weight
Front Springs: Taperleaf 20K w/ shock absorbers w/ maintenance-free elastomer spring pin bushings. Standard with rubber pins except for C500 which has threaded pins. Not available on W900L. W900B use 2866021.	241
Dual power steering gears: 20K TRW TAS65.	60
Power Steering Cooler: Radiator Mounted Air-to-Oil	11

Rear Axle & Equipment

Dual Meritor RT46-164PEH rear axle rated at 46K w/ heavy wall housing. Tandem rear axles.	1,283
Rear Axle Ratio - 4.10.	0
Dual Rear Brakes 16-1/2x7 in. to 46K; Bendix ES-extended service S-cam.	0
Dual Rear Brake Drums: cast.	0
Longer studs for aluminum wheels w/ steel hub pilot wheels.	6
Dual Rear Hubs: Aluminum hub pilot 46K 11-1/4 in. bolt circle.	0
ConMet PreSet Plus Hub package; dual rear axle.	0
Dual Rear axle automatic slack adjusters.	0
Spring Brake: 3030 long stroke dual 30 square inches travel; replaces standard 2-1/2 in. travel. Helps keep brakes in adjustment longer.	4
Bendix 6S/6M anti-lock brake system w/ air traction control (ATC).	6
Driveline: 1 Meritor RPL20 Interaxle; Replacing I/A *Use W/ RPL 25 Main D/L	0
Driver Controlled Differential Lock (Crosslock) for Meritor Axles 40K to 52K forward rear & rear rear axle. Under Speed Interlock is standard on T680.	39
Separate flip valve for dual axles: differential lock or crosslock.	0
Rear suspension: Tandem Hendrickson RT463 46K. 54 in. axle spacing. Steel beams & barpin bushing. 6 in. saddle height. Unladen Height: 11.1 in. Laden Height: 10 in.	1,055

Tires & Wheels

Front tires: Bridgestone M870 315/80R22.5 20PR All Position	94
Rear Tires: Bridgestone M710 Ecopia 11R22.5 14PR. 41.8 in. diameter, drive. 19.5 in. SLR. Smartway certified. Code is priced per pair of tires.	56
Rear Tire Quantity: 8	0
Front Wheel: Alcoa 89U64 22.5X9 AL Ultra ONE Wheel.	-24

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed: 11/7/2018 8:20:55 AM
Effective Date: Jan 1, 2019
Prepared by: Preston Fredrich

Complete

Model Number: T400 Series Conventional.
Quote/DTPO/CO: Q02035278
Version Number: 43.01

Description	Weight
Rear Wheel: Accuride 51408 22.5x8.25 steel	-48
Steel Armor[™] powder coat, hub-pilot mount. 7400lb. maximum rating. 2-hand holes. Air disc brake compatible. Code is priced per pair of wheels.	
Powder coat white steel wheel. Use in conjunction	0
with front, dual front, rear, spare or lift axle wheel code(s). All wheels on chassis must have same finish color.	
Rear Wheel/Rim Quantity: 8	0
Frame & Equipment	
Frame Rails: 10-5/8 x 3-1/2 x 5/16 in. Steel to	329
337 in. to 416 in. Truck frame weight is 2.91 lb.-in. per pair of rails. Section modulus is 14.80, RBM is 1,776,000 in.-lbs per rail. Frame rail availability may be restricted based upon application, axle/suspension capacity, fifth wheel setting, or component/dimensional specifications. The results of the engineering review may result in a change to the requested frame rail. If a change is required Kenworth Application Engineering will advise the dealer of the appropriate material specification for a substitute rail.	
Full Steel Insert: for 10-5/8 in. or 10-3/4 in.	722
Steel 337 in. to 416 in. or 2nd insert for 11-5/8 in. steel frame. Adds 1,149,000 in.-lb to main rail RBM. Truck insert weight is 2.05 lb.-in. per pair of rails. Full frame insert length is equal to wheelbase plus rear frame cutoff plus dimension forward of front axle by model: T660, T680, T800, T880 = 21.26 in.; C500B = bumper setting minus 0.79 in.; W900B = 5.27 in.; W900L = 1.50 in.; W900S = 3.27 in.; T440/T470 50 in. bumper setting = 21.26 in.; T470 73 in. bumper setting = 72.3 in.	
Delete bumper: Requires a bumper setting code.	-94
50 in. Bumper setting. Requires a bumper code.	0
Front mudflaps.	0
Custom Frame Layout: one chassis	0
CFL C/M LAY OUT SIMILAR TO 188301 CFL F/T LAY OUT SIMILAR TO 188301 CFL DEF LAY OUT SIMILAR TO 188301 CFL A/D LAY OUT SIMILAR TO 188301 CFL A/T LAY OUT SIMILAR TO 188301	
Battery box cantilever aluminum BOC with	8
fiberglass cover.	
Battery box location: LH Side.	0
T470,C5, T6, T8 non-polished DPF/SCR or CNG cover	0
diamond plate w/ step. For use w/ 2010 or later exhaust systems. For T8, use extended length non-polished battery box on opposite rail to match the length of under cab components. End plates will be painted standard black frame color.	
Width across front tires exceeds 102 inches.	0
Dealer to review delivery constraints w/transporter.	
Rear mudflap arms: Betts B-25 standard-duty,	0
straight. Includes B1732 mounting brackets as standard.	

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed: 11/7/2018 8:20:55 AM
Effective Date: Jan 1, 2019
Prepared by: Preston Fredrich

Complete

Model Number: T400 Series Conventional.
Quote/DTPO/CO: Q02035278
Version Number: 43.01

Description	Weight
Rear mudflap shields: White plastic antisail w/ Kenworth logo.	0
Square end-of-frame w/o crossmember; non-towing.	0
Special frame drill: dealer to provide drawing with dimensions and revision level. Acceptable hole diameters range from 10.2 mm to 40.4 mm. Preferred file format is .pdf. Not for use for rear suspension, fifth wheel or other published frame drilling code. Does not replace clear frame space requests or custom frame layout.	0

Fuel Tanks & Equip

Fuel Tank: 90 US gallon 28.5in. aluminum under replace. Class 8 fuel tank includes an anti-siphon device on the filler neck.	0
Small round DEF tank. 11 gallons of usable volume. The DEF tank will be located on the side you specified. If you have specific configuration or body builder concerns, please utilize the Custom Frame Layout option. Standard capacity is calculated by fuel capacity of the vehicle and will accommodate two diesel fill-ups for every DEF fill-up. For 1:1 DEF fuel fill ratio, add 7889204.	0
Welded-in fitting w/ gasket & cover plate for mounting customer-installed fuel tank heater.	0
Plate and Gasket moved to rear of tank	0
Standard DEF to fuel fill ratio: 2:1 or greater.	0
Anti-siphon device swaged in place. For any number of fuel tanks.	1
DEF tank location is on the RH.	0
Location: 90 gal fuel tank LH under cab	0

Cab & Equipment

Cab: Curved Glass Conventional. Cab Includes aluminum & fiberglass fully hucked cab w/ all aluminum bulkhead doors & continuous stainless steel piano-style door hinges. Single electric horn standard. Incandescent exterior lights include diagnosable bulb detection and warning. Trailer cable on tractors includes integrity detection. Standard features include multiplex wiring for interior lights, automated pre-trip inspection, short and open check diagnostics. Warning alarm will sound when lights are left on.	0
Hood: Sloped Aerodynamic T440 Hood. Includes hood and mounted grille, split fenders w/ mudflaps, & separate bumper.	0
Cab heater: W/integral defrosters & A/C 45,000 btu cab heater. No sleeper heater/AC. Includes 5 mode rotary control. T660 include filter media.	0
Steering wheel: 18 in. 4-spoke.	0
Adjustable telescoping tilt steering column.	10

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed: 11/7/2018 8:20:55 AM
Effective Date: Jan 1, 2019
Prepared by: Preston Fredrich

Complete

Model Number: T400 Series Conventional.
Quote/DTPO/CO: Q02035278
Version Number: 43.01

Description	Weight
Information for customer-installed PTO Chelsea 277. 10-bolt. Available only with Allison 3000/4000 series transmissions.	0
30 Amp Power Lead With Ground. Wired Through Accessory To Behind Rider Seat.	0
KW Driver Information Center: Includes fuel economy, RPM display, trip information, truck information, diagnostics, gear display, alarm clock.	0
Instrument package: Includes speedometer, tachometer, fuel gauge, engine coolant temperature gauge, engine oil pressure, voltmeter. Class 8 also includes primary & secondary air reservoir gauges & an air application gauge. DEF level gauge and warning lamp are included with 2010+ engines. Engine hour meter and outside air temperature readouts are standard. Primary read out will be MPH. Add 8240620 to switch primary scale to KPH in Canada.	0
Large flat panel on dash For customer-installed controls. Reduces gauge count by 6.	0
Cab Interior: Summit. T440/T470 Only. Includes smooth upholstered side & back panels w/stitched accent lines, upholstered door pads, full vinyl headliner, black dash panels & black rubber floor mats.	0
Interior color: Slate Gray w/trim Dark Slate Gray	0
Driver seat: Kenworth Air cushion Plus HB cloth. Standard features includes 7 in. fore and aft slide adjustment w/isolator, 6- 23 degree recline, air suspension with cover, dual armrests, and single chamber air lumbar support. Seat cushion is 20 inches wide w/ 2-position tilt and 2-position front cushion extension. Seat material has a horizontal stitch pattern and is 2-tone in color. Seat back is carpeted and includes a map pocket. Seat is manufactured by National. Includes inside visor and retractable 3-point matching seat belts. Grey seat belts.	0
Rider seat: Kenworth Toolbox Plus HB cloth. Standard features include fixed base and backrest, tool box seat base w/ door, and dual armrests. Seat cushion is 19.5 inches. Seat material has a horizontal stitch pattern and is 2-tone in color. Seat back is carpeted with a map pocket. Seat is manufactured by National. Includes inside visor and retractable 3-point matching seat belts. Grey seat belts.	0
Seat color: Dark Slate Gray.	0
Kenworth Radio with AM/FM/WB/CD/USB and Bluetooth	4
Non-self cancelling turn signal: W/column-mounted headlight dimmer switch & intermittent wiper control.	0
Electric LH & RH door locks.	0
Cab access contoured grabhandles, LH/RH.	0
Grabhandle: LH inside door frame above dash.	0
Grabhandle: RH inside door frame above dash.	0
Daylite Door: LH/RH includes RH peeper window	0

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed: 11/7/2018 8:20:55 AM
Effective Date: Jan 1, 2019
Prepared by: Preston Fredrich

Complete

Model Number: T400 Series Conventional.
Quote/DTPO/CO: Q02035278
Version Number: 43.01

Description	Weight
Single air horn under cab.	0
Look-Down, Pass. Door, Stainless 8.5x4.4	0
Dual convex heated mirror 8.5 inch w/ offset mounting below regular mirror.	11
Mirror: Dual Prutsman Lighted Mirrors 7 in. x 16 in. Polished Stainless Steel, Thermostatically Controlled & Lighted. Switch Located On Door Pad.	0
Mirror brackets 8-1/2 ft load width.	0
Rear Cab Stationary Window 17 in. x 36 in.	0
Manual LH & electric-powered RH door window. Switch located on door.	0
One-piece windshield, w/ curved glass.	0
Exterior aerodynamic sunvisor w/ integral marker lights.	0
2 in. rubber wheelwell fender extension.	8
Link Cabmate suspension.	22

Lights & Instruments

Headlamps: Halogen Projector Low Beam, Halogen Complex Reflector High Beam	0
Marker Lights: Five aerodynamic, LED mounted in sunvisor.	0
Turn Signal Lights: Mounted on fender	0
LED Stop, Turn, Tail: With Two LED Backup Lights and With An LED License Plate.	2
Marker Lights: Interrupter Switch. Included in Turn Signal For All Models Except T3. The T3 Switch Is In The Dash.	0
Electric Backup Alarm: Meets SAE J994 & OSHA requirements.	4
Junction Box: Under cab	1
Circuit Breakers: Replacing fuses. Does not apply to any 5-amp fuse box position. Brakers include stop/brake/turn, tail lamp, high & low beams, marker/clearance lamps, horn, fuel heat, gauges, air dryer, HVAC controls, panel lamps. Some circuits will remain fuses.	0

Air Equipment

Air Dryer Bendix AD-IS heated Puraguard	0
Moisture ejection valve w/ pull cable drain.	0
Nylon air tubing in frame & cab, excluding hoses subject to excessive heat or flexing.	0

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed: 11/7/2018 8:20:55 AM
Effective Date: Jan 1, 2019
Prepared by: Preston Fredrich

Complete

Model Number: T400 Series Conventional.
Quote/DTPO/CO: Q02035278
Version Number: 43.01



	Description	Weight
Extended Warranty	Base Warranty - PACCAR PX-9 Engine 24 months / 250,000 miles / 402,336 km / 6250 hours.	0
	Base Warranty - Standard Service Heavy Duty 12 months / 100,000 miles / 160,000 km.	0
Miscellaneous	Ship to Dealer.	0
	GHG Secondary Manufacturer: Does Not Apply	0
	Additional lead time required for off highway & /or specially component truck.	0
Paint	Paint color number(s). N97020 A - L0006 WHITE N97200 FRAME N0001 BLACK	0
	Day Cab Standard Paint	0
	1 - Color Paint - Day Cab Color will be White if no other color is specified.	0
	Base coat/clear coat. The Kenworth Color Selector contains additional instructions, as well as information on Kenworth paint guidelines and surface finish applications. Kenworth is standard with Dupont Imron Elite paint.	0
	Total Weight	15814 lb

Prices and Specifications Subject to Change Without Notice.

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	11/7/2018 8:20:55 AM	Complete	Model Number:	T400 Series Conventional.
Effective Date:	Jan 1, 2019		Quote/DTPO/CO:	Q02035278
Prepared by:	Preston Fredrich		Version Number:	43.01



Presents a Proposal Summary

of the



2100 Plus

Combination Single Engine Sewer Cleaner with Positive Displacement Vacuum System Mounted on a Heavy Duty Truck Chassis

for

City of League City
League City, Texas

Marcus Breidenthal
Tel: 713-823-6107

PRODUCT DESCRIPTION

- 2100i with Roots 824-18" Hg. Blower, 15 Yard Debris body, 1500 Gallons of Fresh Water

STANDARD FEATURES

- 48" x 22" x 24" Curb Side Aluminum Toolbox
- Aluminum Fenders
- Mud Flaps
- Electric/Hydraulic Four Way Boom
- Color Coded Sealed Electrical System
- Remote Pendant Control w/35' Cord
- Intuitouch Electronic Package
- Double Acting Dump Hoist Cylinder
- Handgun Assembly
- 3" Y-Strainer at Water Pump Inlet
- Ex-Ten Steel Cylindrical Debris Tank
- Flexible Hose Guide
- 30 Deg. Sand Nozzle w/Carbide Inserts
- 30 Deg. Sanitary Nozzle w/Carbide Inserts
- 15 Deg. Penetrator Nozzle w/Carbide Inserts
- Nozzle Storage Rack
- Vacuum Tube Storage: Curbside (2) Pipe, Rear Door (2) Pipe
- 1" Nozzle
- 10' Leader Hose
- Flat Rear Door w/Hydraulic Locks and Door Power-up/Down, Open/Close Feature
- Dual 10" Stainless Steel Float Shut Off System/Rear Mounted
- Debris Body Vacuum Relief System
- Debris Deflector Plate
- 60" Dump Height
- Water Sight Gauge DS/PS
- Liquid Float Level Indicator
- Boom Transport Post Storage
- 3" Y-Strainer @ Water Pump w/3" Drain Valve
- Performance Package: (Hyd Variable Flow, Dual PTO's. Dual Hyd. Pumps)
- Stainless Steel Microstrainer
- Blower Air Shift Controls
- Hydraulic Cooling Package
- Midship Handgun Coupling
- Side Mounted Water Pump
- Hose Wind Guide (Dual Roller)
- Hose Footage Counter - Mechanical
- Hose Reel Manual Hyd. Extend/Retract
- Hose Reel Chain Cover (Full)
- Tachometer/Chassis Engine W/Hourmeter
- Circuit Breakers
- LED Lights. Clearance, Back-Up, Stop, Tail & Turn
- Tow Hooks, Front and Rear
- Electronic Back-Up Alarm
- Hydraulic Tank Shutoff Valves
- 7" Vacuum Pipe Package
- Emergency Flare Kit
- Fire Extinguisher 5 Lbs.
- Low Water Alarm with Water Pump Flow Indicator
- Front Joystick Boom Control
- Digital Hose Footage Counter

- Water Pump Hour Meter
- PTO Hour Meter
- Camera System, Rear Only
- Digital Water Pressure Gauge
- Vactor 2100i Body Decal - Multi-Colored
- Chassis Modifications
- Vactor Manual, Partial Manual and USB Version - 1 + Dealer

ADDITIONAL FEATURES

- Roots 824-18" Hg. Blower
- 180 Degree Rotation, 10 Ft. Telescoping Boom x 15 Ft. Hydraulic Extendable
- 80 GPM Variable Flow Water System
- 2500 PSI Water Pressure
- 1" x 800' Piranha Sewer Hose, 2500 PSI
- Hydraulic Extending/Rotating 15" Hose Reel (1" x 800') Capacity
- Module Paint, Dupont Imron Elite - Sanded Primer Base
- Debris Body Flush Out System
- 6" Knife Valve w/Cam-Loc, Rear Door, 6:00 Position
- Centrifugal Separators
- Folding Pipe Rack, Curbside
- Rear Door Splash Shield
- Lube Manifold
- Plastic Lube Chart
- Continuous Water Tank Fill
- Hot Shift Blower Drive
- Wireless Controls, including hose reel controls
- Rotatable Boom Inlet Hose, 10 x 15 RDB
- Rodder System Accumulator- Jack Hammer on/off control w/ manual valve
- Hydro Excavation Kit - Includes Lances, Nozzles, Storage Tray, and Vacuum Tubes
- Automatic Hose Level Wind Guide, Indexing
- High Pressured Hose Reel
- Rodder Pump Drain Valves
- Rear Directional Control, Signal Master LED Arrow Stick, 8 Lights
- Strobe Light, LED, Rear, Federal Signal, Amber
- Rear Beacon Limb Guard
- Worklights (2), LED, 10 x 15 RDB
- Toolbox, Behind Cab
- Digital Water Level Indicator
- Debris Body Level Indicator

Chassis Source - Customer Supplied

Module Paint Match Cab - Yes
Module Paint Color - White
Cab Color - White
Door Stripe Color - None
Chassis Axle - Tandem
Certified Unit Weight Required - No

Customer Total: \$292,877.00

DELIVERY AND LIFETIME TRAINING INCLUDED!!

Price valid for 30 Days from date of 11/12/2018

Product Model: 2100PLUS

Product Model: 2100PLUS

Proposal Date: 11/12/2018

Quote Number: 2018-28583

Price List Date: 7/1/2018

P.O. Number:

Payment Terms:

Proposal Notes:

1. Multiple unit orders will be identical to signed proposal. Changes or deviations to any unit of a multiple unit order will require a new signed proposal.
2. Chassis specifications and data codes for customer supplied chassis must be submitted to and approved by Vactor Manufacturing prior to submittal of customer purchase order
3. All prices quoted are in US Dollars unless otherwise noted.

SIGNED BY:

_____ Date: _____

LIMITED WARRANTY

Limited Warranty. Each machine manufactured by VACTOR/GUZZLER MANUFACTURING (or, "the Company") is warranted against defects in material and workmanship for a period of 12 months, provided the machine is used in a normal and reasonable manner and in accordance with all operating instructions. In addition, certain machines and components of certain machines have extended warranties as set forth below. If sold to an end user, the applicable warranty period commences from the date of delivery to the end user. If used for rental purposes, the applicable warranty period commences from the date the machine is first made available for rental by the Company or its representative. This limited warranty may be enforced by any subsequent transferee during the warranty period. This limited warranty is the sole and exclusive warranty given by the Company.

STANDARD EXTENDED WARRANTIES (Total Warranty Duration)

2100 Series, HXX, Series and Jetters

10 years against water tank leakage due to corrosion. Nonmetallic water tanks are covered for 5 yrs. against any factory defect in material or workmanship.

2100 Series and HXX only

5 years against leakage of debris tank, centrifugal compressor or housing due to rust-through.

2100 Series and Jetters

2 years - Vactor Rodder Pump on all unit serial numbers starting with 13##V#####.

Exclusive Remedy. Should any warranted product fail during the warranty period, the Company will cause to be repaired or replaced, as the Company may elect, any part or parts of such machine that the Company's examination discloses to be defective in material or factory workmanship. Repairs or replacements are to be made at the selling Vactor/Guzzler distributor's location or at other locations approved by the Company. In lieu of repair or replacement, the Company may elect, at its sole discretion, to refund the purchase price of any product deemed defective. The foregoing remedies shall be the sole and exclusive remedies of any party making a valid warranty claim.

This Limited Warranty shall not apply to (and the Company shall not be responsible for):

1. Major components or trade accessories that have a separate warranty from their original manufacturer, such as, but not limited to, trucks, engines, hydraulic pumps and motors, tires and batteries.
2. Normal adjustments and maintenance services.
3. Normal wear parts such as, but not limited to, oils, fluids, vacuum hose, light bulbs, fuses, gaskets.
4. Failures resulting from the machine being operated in a manner or for a purpose not recommended by the Company.
5. Repairs, modifications or alterations without the express written consent of the Company, which in the Company's sole judgment, have adversely affected the machine's stability, operation or reliability as originally designed and manufactured.
6. Items subject to misuse, negligence, accident or improper maintenance.

NOTE The use in the product of any part other than parts approved by the Company may invalidate this warranty. The Company reserves the right to determine, in its sole discretion, if the use of non-approved parts operates to invalidate the warranty. Nothing contained in this warranty shall make the Company liable for loss, injury, or damage of any kind to any person or entity resulting from any defect or failure in the machine.

THIS WARRANTY SHALL BE IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING WITHOUT LIMITATION, ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ALL OF WHICH ARE DISCLAIMED.

This warranty is in lieu of all other obligations or liabilities, contractual and otherwise, on the part of the Company. For the avoidance of doubt, the Company shall not be liable for any indirect, special, incidental or consequential damages, including, but not limited to, loss of use or lost profits. The Company makes no representation that the machine has the capacity to perform any functions other than as contained in the Company's written literature, catalogs or specifications accompanying delivery of the machine. No person or affiliated company representative is authorized to alter the terms of this warranty, to give any other warranties or to assume any other liability on behalf of the Company in connection with the sale, servicing or repair of any machine manufactured by the Company. Any legal action based hereon must be commenced within eighteen (18) months of the event or facts giving rise to such action.

The Company reserves the right to make design changes or improvements in its products without imposing any obligation upon itself to change or improve previously manufactured products.

GUZZLER

VACTOR

VACTOR/GUZZLER MANUFACTURING

1621 S. Illinois Street
Streator, IL 61364

TERMS AND CONDITIONS

ORDERS: All orders are subject to acceptance by Vactor Manufacturing, Inc. or Guzzler Manufacturing, Inc. (hereafter referred to as Vactor). Orders for products not normally carried in stock or requiring special engineering or manufacturing is in every case subject to approval by Vactor's Management.

PRICES: All orders are subject to current prices in effect at the time of order acknowledgement.

F.O.B. Point: Unless otherwise stated, all prices listed are F.O.B. factory.

PAYMENT TERMS: The company's payment terms are due upon receipt, unless otherwise stated. However, until such time as Vactor receives full payment, Vactor shall maintain a purchase money security interest in the product.

CANCELLATION: Orders regularly entered cannot be cancelled except upon terms that will compensate Vactor for any loss or damage sustained. Such loss will be a minimum of 10% of the purchase price.

SHIPMENT: All proposals are based on continuous and uninterrupted delivery of the order upon completion, unless specifications distinctly state otherwise. In the event that agreement is reached for Vactor to store completed items, they will be immediately invoiced to the customer and become due and payable. Storage shall be at the risk of the customer and Vactor shall be liable only for ordinary care of the property.

STORAGE CHARGES: Vactor shall charge the customer at current rates for handling and storing customer's property (e.g. truck chassis) held for more than thirty (30) days after notification of availability for shipment. All customer's property, or third party's property, that is stored by Vactor is at the customer's or other party's risk. Vactor is not liable for any loss or damage thereto caused by fire, water, corrosion, theft, negligence, or any caused beyond its reasonable control.

PERFORMANCE: Vactor shall not be liable for failure to complete the contract in accordance with its terms if failure is due to wars, strikes, fires, floods, accidents, delays in transportation or other causes beyond its reasonable control.

EXPERIMENTAL WORK: Work performed at customer's request such as sketches, drawings, design, testing, fabrication and materials shall be charged at current rates.

SKETCHES, ENGINEERING DRAWINGS, MODELS and all preparatory work created or furnished by Vactor, shall remain its exclusive property; and no use of same shall be made nor may ideas obtained therefrom be used except with the consent of and on terms acceptable to Vactor.

TAXES: The pricing attached does not include Federal, State or local taxes which are the buyer's responsibility. However, Vactor/Guzzler Manufacturing, Inc. shall be responsible for Federal Excise Tax (F.E.T.) unless it is separately stated on the invoice and added to the selling price. If F.E.T. is not separately stated on the invoice it has not been included in the price and Vactor/Guzzler will pay any F.E.T. due itself and bear the cost of the tax. Any refunds or adjustments to the F.E.T. in such cases belong to Vactor/Guzzler.

PRODUCT IMPROVEMENTS: Vactor reserves the right to change manufacturing specifications and procedure in accordance with its product improvement policy.

MOUNTING PRICES: Mounting prices assume normally factory installation on a truck chassis suitable for the unit purchased. Relocation of batteries, fuel tanks, mufflers, air tanks, etc. will be an additional charge, billed at the standard factory labor rate.

WARRANTY: Vactor warrants its products to be free from defects in material and workmanship, subject to the limitations and conditions set forth in its current published warranty. Other than those expressly stated herein. THERE ARE NOT OTHER WARRANTIES OF ANY KIND EXPRESS OR IMPLIED, AND SPECIFICALLY EXCLUDED BUT NOT BY WAY OF LIMITATION, ARE THE IMPLIED WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE AND MECHANABILITY.

IT IS UNDERSTOOD AND AGREED THE SELLER'S LIABILITY WHETHER IN CONTRACT, IN TORT, UNDER ANY WARRANTY IN NEGLIGENCE OR OTHERWISE SHALL NOT EXCEED THE RETURN OF THE AMOUNT OF THE PURCHASE PRICE PAID BY THE PURCHASER AND UNDER NO CIRCUMSTANCES SHALL SELLER BE LIABLE FOR SPECIAL, INDIRECT, INCIDENTAL OR CONSEQUENTIAL DAMAGES. THE PRICES STATED FOR THE EQUIPMENT IS A CONSIDERATION IN LIMITING SELLER'S LIABILITY. NO ACTION REGARDLESS OF FORM, ARISING OUT OF THE TRANSACTION OF THE AGREEMENT MAY BE BROUGHT BY PURCHASER MORE THAN ONE YEAR AFTER THE CAUSE OF ACTION HAS ACCURED.

SELLER'S MAXIMUM LIABILITY SHALL NOT EXCEED AND BUYER'S REMEDY IS LIMITED TO EITHER (I) REPAIR OR REPLACEMENT OF THE DEFECTIVE PART OF PRODUCT, OR AT SELLER'S OPTION (II) RETURN OF THE PRODUCT AND REFUND OF THE PURCHASE PRICE AND SUCH REMEDY SHALL BE BUYER'S ENTIRE AND EXCLUSIVE REMEDY.

TERMS AND CONDITIONS

This agreement shall be construed according to the laws of the State of Illinois. Failure at anytime by Vactor to exercise any right of the Company may have under this agreement shall not constitute a waiver-thereof nor prejudice Vactor's right to enforce it thereafter.

This order, including the above terms and conditions, contains the complete and final agreement between the parties hereto and no other agreement in any way modifying any of said terms and conditions will be binding on Vactor unless in writing and agreed to by an authorized representative of Vactor.

I agree with the above terms and conditions:

Date: _____



CONTRACT PRICING WORKSHEET
For Standard Equipment Purchases

Contract
No.:

EM06-17

Date
Prepared:

6/1/2018

This Worksheet is prepared by Contractor and given to End User. If a PO is issued, both documents MUST be faxed to H-GAC @ 713-993-4548. Therefore please type or print legibly.

Buying Agency:	City of League City	Contractor:	Associated Supply Company (DBA ASCO)
Contact Person:	Cecil Bowery	Prepared By:	Skipper Robinson
Phone:	281-554-1089	Phone:	(832) 316-2507
Fax:		Fax:	(713) 649-5571
Email:	cecil.bowery@leaguecitytx.gov	Email:	srobinson@ascoeq.com

Product Code:	15C	Description:	Gradall XL4100 V 6x4 Truck Mounted Excavator
---------------	-----	--------------	--

A. Product Item Base Unit Price Per Contractor's H-GAC Contract:	\$390,165.44
--	--------------

B. Published Options - Itemize below - Attach additional sheet if necessary - Include Option Code in description if applicable
(Note: Published Options are options which were submitted and priced in Contractor's bid.)

Description	Cost	Description	Cost
Aux Hyd. Plumbing - Motor Spool	\$2,900.00	Bucket-66" Ditching w/ Bolt On Cutting Edge	\$5,233.00
Beacon Light LED Upper w/ brnch gd	\$1,070.00	Fixed Thumb Grapple	\$9,408.00
Low Pressure Aux Return to Tank	\$539.00	Extra set of keys	\$20.00
Lube Chart - Upper	\$343.00	Printed set of manuals	255
Air conditioning Installation - Chassis	\$2,410.00	Standard Warranty: 12 months or 1500 hours	Included
Beacon Light LED chassis w/ brnch gd	1070		
Left Hand Rear Step	\$512.00		
Lube Chart - Chassis	\$372.00		
Tilt steering column - chassis	\$872.00		
		Subtotal From Additional Sheet(s):	
		Subtotal B:	25004

C. Unpublished Options - Itemize below - Attach additional sheet if necessary.
(Note: Unpublished options are items which were not submitted and priced in Contractor's bid.)

Description	Cost	Description	Cost
		Subtotal From Additional Sheet(s):	
		Subtotal C:	0

Check: Total cost of Unpublished Options (C) cannot exceed 25% of the total of the Base Unit Price plus Published Options (A+B). For this transaction the percentage is: 0%

D. Total Cost before any other applicable Charges, Trade-Ins, Allowances, Discounts, Etc. (A+B+C)

Quantity Ordered:	1	X Subtotal of A + B + C:	415169.44	=	Subtotal D:	415169.44
-------------------	---	--------------------------	-----------	---	-------------	-----------

E. Trade-Ins / Special Discounts / Other Allowances / Freight / Installation / Miscellaneous Charges

Description	Cost	Description	Cost
Factory Freight	\$7,100.00		
Local Delivery	\$400.00		
		Subtotal E:	7500

Delivery Date:	90-120 Days	F. Total Purchase Price (D+E):	422669.44
----------------	-------------	--------------------------------	-----------